Lindy Extender HDMI 4K30 & IR Cat.6 70m avec PoC & Loop Out

Marque : Lindy

Code produit: 38208

Nom du produit : Extender HDMI 4K30 & IR Cat.6 70m avec PoC & Loop Out



- Étend les signaux HDMI et IR jusqu'à 70 m en utilisant un câble Cat.6
- Prend en charge des résolutions allant jusqu'à 3840x2160@30Hz 4:4:4 8bit
- Dispose d'une sortie HDMI en boucle sur l'émetteur pour une surveillance locale
- Prise en charge de l'alimentation par le câble de catégorie 6, une seule alimentation est nécessaire

Extender HDMI 4K30 & IR Cat.6 70m avec PoC & Loop Out
Lindy Extender HDMI 4K30 & IR Cat.6 70m avec PoC & Loop Out. Type: Émetteur et récepteur AV, Résolution maximale: 3840 x 2160 pixels, Types de câbles soutenus: Cat6. Technologie de connectivité: Avec fil. Tension de fonctionnement: 12 V, Courant d'entrée: 1 A. Largeur: 79,5 mm, Profondeur: 69 mm, Hauteur: 16,5 mm. Largeur du colis: 200 mm, Profondeur du colis: 70 mm, Hauteur du colis: 113 mm



Caractéristiques	
Type *	Émetteur et récepteur AV
Résolution maximale *	3840 x 2160 pixels
Types de câbles soutenus	Cat6
Distance de transfert maximale	70 m
Jeu de composants	GSV1001
Taux de d'actualisation maximal	60 Hz
Données EDID (Extended display identification data)	✔
Canaux de sortie audio	7.1 canaux
Résolutions graphiques prises en charge	1920 x 1080 (HD 1080), 3840 x 2160
Bande passante	10,2 Gbit/s
HDCP	✔
Matériel	Métal
Version HDCP	1.4
Couleur du produit	Noir
Certification	CE, FCC, RoHS, REACH

Connectivité	
Technologie de connectivité *	Avec fil
ports d'entrée RJ-45	1
ports de sortie RJ-45	1
Entrée HDMI	1
Nombre de sorties HDMI	2
Version HDMI	1.4
Commande (IR) entrée	1

Connectivité	
Commande (IR) sortie	1

Puissance	
Tension de fonctionnement	12 V
Courant d'entrée	1 A

Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-20 - 60 °C
Humidité relative de fonctionnement (H-H)	20 - 90%

Poids et dimensions	
Largeur	79,5 mm
Profondeur	69 mm
Hauteur	16,5 mm
Poids	130 g

Informations sur l'emballage	
Largeur du colis	200 mm
Profondeur du colis	70 mm
Hauteur du colis	113 mm
Poids du paquet	414 g

Contenu de l'emballage	
Adaptateur secteur fourni	✔
Manuel d'utilisation	✔
Récepteur infra-rouge compris	✔

Détails techniques	
Certificats de conformité	CE, REACH, RoHS

4002888382083

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 23-SEP-2026. Prints or copies of Information are only valid on the printed Publication date