D-Link DGS-1520-52/E commutateur réseau Géré L3 10G Ethernet (100/1000/10000) 1U Noir

Marque : D-Link

Code produit: DGS-1520-52/E

Nom du produit : DGS-1520-52/E



D-Link DGS-1520-52/E. Type de commutateur: Géré, Banc de commutateurs: L3. Type de port Ethernet RJ-45 de commutation de base: 10G Ethernet (100/1000/10000), Quantité de ports Ethernet RJ-45 de commutation de base: 50. Répertoire MAC: 16384 entrées, Capacité de commutation: 176 Gbit/s. Grille de montage, Format: 1U

Caractéristiques de gestion	
Type de commutateur *	Géré
Banc de commutateurs	L3
Gestion basée sur le web	✔

Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	50
Type de port Ethernet RJ-45 de commutation de base *	10G Ethernet (100/1000/10000)
Quantité de ports .Gigabit Ethernet (copper)	48
Quantité de ports Ethernet 10 G (cuivre)	2
Quantités d'emplacements de module SFP+	2
Ports Fibre Channel	2
Connecteur de fibre optique	SFP+

Réseau	
Soutien 10G *	✔
Assistance contrôle des flux	✔
Agrégation de lien	✔
Auto MDI/MDI-X	✔
Protocles Spanning Tree (STP)	✔
Fonction HOL contre la saturation des en-têtes de file	✔
Support VLAN	✔

Transmition des données	
Capacité de commutation *	176 Gbit/s
Taux de transfert	130,95 Mpps
Répertoire MAC *	16384 entrées
Enregistrement-et-réémission	✔
Route statique	✔
Support de trames étendues (Jumbo Frames)	✔
Trames géantes	12288

Sécurité	
Filtrage IGMP	✔
Protection en boucle	✔
Filtrage/protection BPDU	✔

Protocoles	
Protocole d'enregistrement GARP VLAN (GVRP)	✔
Protocole de routage	OSPF, RIP, RIPng, VRRP

Design	
Grille de montage *	✔
Empilable *	✔
Format	1U
Couleur du produit	Noir

représentation / réalisation	
Empilage physique (unités)	8
Empilage virtuel (unités)	32
Niveau sonore	56,8 dB
Temps moyen entre pannes	364888 h

Puissance	
Source d'alimentation *	Secteur
Alimentation redondante (RPS)	✔
Tension d'entrée AC	100 - 240 V
Consommation (max)	51,2 W

PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✘

Conditions environnementales	
Température d'opération	-5 - 50 °C
Température hors fonctionnement	-40 - 70 °C
Humidité relative de fonctionnement (H-H)	10 - 95%
Taux d'humidité relative (stockage)	5 - 95%
Dissipation thermique	174,6 BTU/h

Poids et dimensions	
Largeur	441 mm
Profondeur	207,4 mm
Hauteur	44 mm
Poids	2,78 kg

Durabilité	
Conformité à la durabilité	✔

Certificat	
Certificats de conformité	BSMI, CE, Federal Communications Commission (FCC)

790069472039

0790069472039

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 23-SEP-2026. Prints or copies of Information are only valid on the printed Publication date