D-Link ES-1005C/E Non-géré Fast Ethernet (10/100) Bureau Blanc

Marque : D-Link

Code produit: DES-1005C/E

Nom du produit : ES-1005C/E



D-Link ES-1005C/E. Type de commutateur: Non-géré. Type de port Ethernet RJ-45 de commutation de base: Fast Ethernet (10/100), Quantité de ports Ethernet RJ-45 de commutation de base: 5. Full duplex. Répertoire MAC: 2000 entrées, Capacité de commutation: 1 Gbit/s. Standards réseau: IEEE 802.2, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Voltage d'entrée DC: 5 V. Connecteur d'alimentation: DC-in jack. Format: Bureau



Caractéristiques de gestion	
Type de commutateur *	Non-géré
Connectivité	
Quantité de ports Ethernet RJ-45 de commutation de base *	5
Type de port Ethernet RJ-45 de commutation de base *	Fast Ethernet (10/100)
Connecteur d'alimentation	DC-in jack
Réseau	
Standards réseau *	IEEE 802.2, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Soutien 10G *	✗
Full duplex	✓
Assistance contrôle des flux	✓
Auto MDI/MDI-X	✓
LAN Ethernet : taux de transfert des données	10,100 Mbit/s
Négociation automatique	✓
Transmition des données	
Capacité de commutation *	1 Gbit/s
Taux de transfert	0,74 Mpps
Répertoire MAC *	2000 entrées
Enregistrement-et-réémission	✓
Support de trames étendues (Jumbo Frames)	✓
Taux de transfert des paquets (100 Mbps)	148800 pps
Taux de transfert des paquets (10 Gbps)	14880 pps
Mémoire cache de paquet	0,093 Mo

Design	
Grille de montage *	✗
Empilable *	✗
Format	Bureau
Couleur du produit	Blanc
Voyants	Activité, Liaison, Énergie, Vitesse
représentation / réalisation	
Sans ventilateur	✓
Temps moyen entre pannes	1785631 h
Puissance	
Source d'alimentation *	CC
Voltage d'entrée DC	5 V
Courant d'entrée	0.55 A
Consommation (max)	0,784 W
PoE (alimentation via le port Ethernet)	
Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✗
Conditions environnementales	
Température d'opération	0 - 40 °C
Température hors fonctionnement	-40 - 70 °C
Humidité relative de fonctionnement (H-H)	10 - 90%
Taux d'humidité relative (stockage)	5 - 95%
Dissipation thermique	0,406 BTU/h
Poids et dimensions	
Largeur	88 mm
Profondeur	48 mm
Hauteur	21,4 mm
Poids	43,4 g

790069478574

0790069478574

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 23-SEP-2026. Prints or copies of Information are only valid on the printed Publication date